

# *Econo Dunker*

## SAFETY RULES

1. Keep *Econo Dunker* away from electricity.
2. Keep water level filled to at least 8" from top of tank.
3. Never leave a filled Dunk Tank unattended by an adult.  
When tank is unattended, always drain water.
- \*4. Keep all non-swimmers and anyone less than 5' tall out of tank. *Weight limit 250 lbs.*
- \*5. To keep from slipping, always wear tennis shoes.
6. Advise dunkee to move towards the front of the tank when coming up out of the water to avoid hitting head on the seat.
7. Only one person at a time allowed on the seat or in the tank.
8. Never use baseballs or other hard balls.
9. Never stand on seat.
10. When sitting on the seat, keep hands on knees and sit forward.
11. Do not hit target with hands.
12. Do not operate *Econo Dunker* during a storm.
13. Periodically, check tank and trailer frame for sharp edges.

# *Econo Dunker*

## **Instructions**

### ***TO TRANSPORT***

1. The Econo Dunker can fit into the bed of most trucks on the market. It will take 2-3 people to lift it into the truck.
2. The Econo Dunker is equipped with dolly wheels on the frame for easy movement when on the ground.

***DO NOT ATTEMPT TO LIFT or MOVE THE DUNK TANK WHEN IT IS FILLED WITH WATER!***

### ***SET UP***

1. Select a level area for set up.
2. Roll to set up area. (NOTE: Trailer and tank are one unit, do not try to separate!)
3. Slowly lift up and set tank upright. (Be careful not to drop tank onto its bottom.)
4. Position wing out into position. **NOTE: The wing MUST BE STRAIGHT out from the tank frame. If it is at an angle the trigger will not work properly.** Make sure the stabilizing rods on the bottom of the wing are staked down so the wind does not move it as this will cause the target arm to jam.
6. Check drain plug to make sure it is tight and then fill tank to the top with water (approx. 500 gallons).
7. Place the flattened end of the arm into the trigger mechanism. Put the other end through the square tubing on the wing and through the hole in the canvas. Make sure the arm drops into the slot on the side of the frame. Insert the target into the end of the arm so the pin holes line up. Insert the clip pin.
8. Place one hand on the front of the seat and push down. With the other hand "test" the target to see that it works properly.
9. **REVIEW SAFETY RULES!!**

## ***Econo Dunker***

### ***OPERATION***

- 1.** Check to see that seat is properly locked and is released when the target is pressed. Be sure to show this operation to the person who will be on the tank as they will need to know how to reset the seat and trigger mechanism each time it is released, before they get back onto the seat. ***Please remind the dunkee to keep their hands on their knees and sit forward on the seat.***
- 2.** Use **ONLY** the balls that came with the Econo Dunker.
- 3.** Monitor water level to keep it full.

### ***TAKE DOWN***

- 1.** As soon as you are finished using the dunker, open the drain and let the tank empty.
- 2.** Disassemble the wing and place in tank. Then slowly tilt tank back onto its wheels.
- 3.** Place seat in its "up" position and lock.
- 4.** Place target, target arm, and balls safely in tow vehicle.